

Safety Data Sheet acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

* 1 Identification

- Product identifier

- **Trade name:** HTS50 Heavy Duty Pipe Sealant with PTFE
- **Synonyms:** HTS50
- **Part number:** HTS50
- **Relevant identified uses of the substance or mixture** Thread sealant

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**

SPX Hydraulic Technologies
5885 11th Street
Rockford, IL 61109
Tel: (800) 541-1418
Fax: (800) 288-7031
Website: www.spxhydraulictech.com
E-mail: info@spxhydraulictech.com

- **Information department:** Product safety department

- **Emergency telephone number:**

United States: 1-800-424-9300
International: +1-703-527-3887

* 2 Hazard(s) identification

- Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07

- **Signal word** Warning

- Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P264 Wash thoroughly after handling.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a poison center/doctor if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:

- NFPA ratings (scale 0 - 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

(Contd. of page 1)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* **3 Composition/information on ingredients**- **Chemical characterization: Mixtures**- **Description:** Mixture of the substances listed below with nonhazardous additions.- **Dangerous components:**

	Cellulose Acetate Butyrate	5-10%
	Hydrophobic silica	5-10%
80-15-9	Cumene hydroperoxide	1-5%
128-44-9	Saccharin	1-5%
609-72-3	N,N-dimethyl-o-toluidine	≤ 1.00%

* **4 First-aid measures**- **Description of first aid measures**- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.- **After swallowing:** Immediately call a doctor.- **Information for doctor:**- **Most important symptoms and effects, both acute and delayed** No further relevant information available.- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* **5 Fire-fighting measures**- **Extinguishing media**- **Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture** No further relevant information available.- **Advice for firefighters**- **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Wear fully protective suit.

* **6 Accidental release measures**- **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Wear protective clothing.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

(Contd. of page 2)

7 Handling and storage**- Handling:****- Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities**- Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions:

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters**- Components with limit values that require monitoring at the workplace:****80-15-9 Cumene hydroperoxide**

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls**- Personal protective equipment:****- General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:

Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties**- Information on basic physical and chemical properties****- General Information****- Appearance:****- Form:**

Viscous

- Color:

White

- Odor:

Characteristic

- Odour threshold:

Not determined.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

(Contd. of page 3)

- pH-value:	Not determined.
- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	200 °C (392 °F)
- Flash point:	131 °C (268 °F)
- Flammability (solid, gaseous):	Not applicable.
- Ignition temperature:	
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure at 20 °C (68 °F):	0.7 hPa (1 mm Hg)
- Density:	Not determined.
- Relative density	Not determined.
- Vapour density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	0.4 %
- Water:	0.1 %
- VOC content:	0.4 %
	3.7 g/l / 0.03 lb/gl
- Solids content:	65.8 %
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:****Cellulose Acetate Butyrate**

Oral	LD50	>6400 mg/kg (rabbit)
Dermal	LD50	>1000 mg/kg (rabbit)

80-15-9 Cumene hydroperoxide

Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)

128-44-9 Saccharin

Oral	LD50	1280 mg/kg (rat)
------	------	------------------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

(Contd. of page 4)

609-72-3 N,N-dimethyl-o-toluidine

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- Carcinogenic categories**- IARC (International Agency for Research on Cancer)**

9002-84-0	Polytetrafluoroethylene	3
-----------	-------------------------	---

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information**- Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- Behavior in environmental systems:

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- Additional ecological information:**- General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

13 Disposal considerations**- Waste treatment methods**

- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information**- UN-Number**

- **DOT, ADN, IMDG, IATA** not regulated

- UN proper shipping name

- **DOT, ADN, IMDG, IATA** not regulated

- Transport hazard class(es)

- **DOT, ADN, IMDG, IATA**
- **Class** not regulated

- Packing group

- **DOT, IMDG, IATA** not regulated

- Environmental hazards:

- **Marine pollutant:** No

- Special precautions for user

Not applicable.

- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

(Contd. of page 5)

- UN "Model Regulation": -

***15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

80-15-9 Cumene hydroperoxide

ethylene glycol

- **TSCA (Toxic Substances Control Act):**

Polyethylene glycol dimethacrylate

Polytetrafluoroethylene

Cumene hydroperoxide

Saccharin

N,N-Diethyl-P-Toluidine

Propylene glycol

Hydrocarbon wax

N,N-dimethyl-o-toluidine

ethylene glycol

1,4-naphthoquinone

Deionized water

- **Proposition 65**- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

ethylene glycol

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Safety, Health and Environmental Affaires- **Contact:** Safety, Health and Environmental Affaires- **Date of preparation / last revision** 05/20/2015 / 22- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/20/2015

Reviewed on 05/20/2015

Trade name: HTS50 Heavy Duty Pipe Sealant with PTFE

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. of page 6)

- * **Data compared to the previous version altered.**